



HARDTAPE®EXTERNAL BAY

WITH USB 2.0 & FIREWIRE OR SATA INTERFACE









HardTape® External USB & FireWire or SATA Bay

The perfect accessory to fully integrate HardTape/MediaPac/SolidTape into your workflow. The external SATA bay allows you access to the 50+MB/s transfer rates of the latest HardTape cartridges. The USB 2.0/FireWire 400 combo bay is great for attachment to computers, NLE's, DVR/PVR's, and other devices with inconvenient rear panel connectors. Both bays provide "hot-swap" capability with fast data transfer rates that allow editing directly to/from the cartridge and can be mounted horizontally or vertically to fit any workspace.

Features	
Capacity	Accepts any HardTape, SolidTape, or MediaPac "Classic" cartridge
Interface	USB 2.0 & FireWire 400 or SATA
Max. Sustained Transfer Speed	FireWire = 43MB/s (345 Mbps) USB = 25MB/s (200 Mbps) SATA = 133MB/s (1.0 Gbps)
Dimension (LxWxH)	8.8 x 5.3 x 1.5 inches 224 x 134 x 38 mm
Weight	External Bay: 2 lbs / 0.9 kg Complete Kit: 4 lbs / 1.8 kg
Material	Aluminum Outer Case Plastic ABS (UL94HB) Panels
Power Source	External Universal Switching Power Adapter (12V 1.5A / 5V 1.5A)
Complete Kit Includes	External Bay; Power Supply; USB A to B Cable & FireWire 6P/6P Cable or SATA Cable; Mounting Stand; Manual

UL, FCC, CE, TUV Certified









AUDAVI Corporation

1430 Tully Road; Suite 416 San Jose, CA 95122

Toll Free: 877-947-0830
Phone: 408-947-8300
Fax: 408-947-8333
Email: info@audavi.com
Website: www.audavi.com
CAGE: 3DJV02 DODAAC: Q92265

©2002—2010 All rights reserved. HardTape, MediaPac, and SolidTape are trademarks of AUDAVI Corporation. All other trademarks are registered with their respective companies. HardTape, MediaPac, and SolidTape features and specifications subject to change without notice.